


# AP One Rugged

Case Durable  
Price Unbeatable



The AP One Rugged is made for times where you need Wi-Fi in **extreme environments**.

Its tough exterior allows for smooth operation in **-40°F/-40°C** to **149°F/65°C** environments.



Power the device normally through **Power over Ethernet** for less cable management, or an industrial **microfit connector** for a secure and durable power option.

It's **resistant to shock, vibrations** and **electromagnetic waves** with the certifications to prove it.




The **DIN rail mount system** allows for flexible deployment, no matter if it's on a wall, on a pole or on the ceiling.





## Take full control of your network


This isn't just your everyday access point. With **Wi-Fi mesh** support, you can eliminate blindspots in your network, and easily control all your devices with InControl 2.



## Ethernet available whenever you need it

It's not just limited to simply providing Wi-Fi either. Boost your devices with wired connections through its 3 GE ports. Having options gives you the power to deploy however you want.

# AP One Rugged



## Specifications

<b>Ethernet Port</b>	3x 10/100/1000M Ethernet	<b>Certifications</b>	FCC, CE, IC, E-Mark, RoHS, Railway Certification: EN 50155, Railway Certification: EN 50121-3-2, Railway Certification: EN 50121-4, Vibration & Shock: EN 61373
<b>Wi-Fi Standard</b>	Simultaneous Dual-Band (2.4GHz / 5GHz) Wi-Fi 5 2X2 MIMO	<b>Warranty</b>	1-Year Limited Warranty
<b>Data Rates</b>	2.4 GHz: up to 300Mbps 5 GHz: up to 866Mbps	<b>Network</b>	Bridge Mode Router (NAT) Mode Mesh Wireless Distribution System (WDS) Support for PPPoE, Static IP, DHCP Management VLAN Spanning Tree Protocol
<b>Channel Width</b>	20/40/80 MHz	<b>Radio</b>	Multiple SSID Auto Channel Selection Transmit Power Adjustment Neighbor AP Detection
<b>Recommended Concurrent Users per Radio</b>	60	<b>AP Security</b>	Open WPA/WPA2/WPA3-Personal WPA/WPA2-Enterprise
<b>SSID</b>	16	<b>Device Management</b>	Web Administrative Interface InControl Cloud Management Peplink AP Controller SNMP v1, v2c and v3
<b>Transmit Power</b>	2.4GHz: 17dBm 5GHz: 17dBm		
<b>Antenna</b>	External Omni Directional Antennas 2x 3dBi - 2.4GHz 2x 3dBi - 5GHz		
<b>Connector type</b>	2x RP-SMA Wi-Fi Antenna connectors		
<b>Power Input</b>	10V - 30V DC 802.3at PoE		
<b>Power Consumption</b>	13w (max.)		
<b>Enclosure</b>	Ruggedized Metal		
<b>Dimension</b>	4.8 x 4.2 x 1.4 inches / 122.1 x 107 x 35 mm		
<b>Weight</b>	0.8 pounds / 365 grams		
<b>Operating Temperature</b>	-40°- 149° F / -40°- 65° C		
<b>Humidity</b>	15% - 95% (non-condensing)		

Specifications are subject to change without notice.

## Specifications

### Client Management

Per SSID  
VLAN with QoS (802.1p/802.1q)  
Bandwidth Control  
MAC Address Filtering  
Layer 2 Client Isolation  
Limit on Max. Number of Clients

Per Client  
VLAN with RADIUS  
VLAN with VLAN  
Pool Bandwidth Control  
Multicast Filter  
IGMP Snooping/Multicast Enhancement

### Captive Portal by InControl

#### Package Contents

AP One Rugged,  
1 x 12V2A Power Supply (ACW-632)  
2 x Dual Band Wi-Fi Antennas (ACW-342)

## Ordering Information

### Product Code

APO-AC-RUG

### Description

Wi-Fi 5 2x2 MIMO Access Point

## Featured Add-on

### Product Code

SVL-413

### Description

EssentialCare (1-Year) for AP One Rugged

SVL-513

EssentialCare (2-Year) for AP One Rugged

ACW-DIN-BR1-MINI

DIN Rail Mount for BR1 Mini / AP One Rugged